

412263

# RESTORA ANTIMOHO BLANCA

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017



FAMILY PINTURAS PLASTICAS

LINE LINEA MATE

## DESCRIPTION AND NATURE

Excellent plastic paint with a velvety matte finish, suitable for economical work due to its excellent coverage. With antimould additive.

## USAGES

Indoors/Outdoors

Cement

Plaster

Brick

Brick

Plaster

Humid zones, cellars, humid houses.

## PROPERTIES

Does not spread flame  
Fungus and seaweed protector  
Low surface tension  
Velvety flat finish  
Excellent opacity once dry  
Minimum splattering  
Good penetration  
Faint odour  
Does not turn yellow  
Does not spread flame  
Good applicability  
Does not turn yellow

## TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA ANTIMOHO BLANCA
Finish	Matt
Specific weight	1,56± 0,05 kg/l
Viscosity	111 +/- 15 PO
Solids in volume	39± 1
Solids in weight	62± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,29 g/l
Aproximated performance by coat	9-11 m <sup>2</sup> /L

Dry to touch	(20°C RH: 60%): -To touch: 1h. -Washing: 25-30 days
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	White.

## SURFACE PREPAIRING

French norm DTU 59.1

### New surfaces

Cement mortars:

1. Wait until fully hardened (min. 30 days).

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017

2. Clean off possible efflorescence with an abrasive jet.
3. Neutralise alkaline surfaces.
4. For polished surfaces: sand down to open the grain.
5. Clean any unusual products from the base.
6. Fix crumbling bases using fixative.
7. Fill in any holes in the base.

Plaster:

1. Wait until the plaster is dry (maximum 20% humidity).
2. Clean any unusual products from the base.
3. Clean off possible efflorescence with an abrasive jet.
4. Control the absorbency of the base using a sealer, fixative or a diluted coat of the same product.
5. For polished surfaces: sand down to open the grain.
6. Fix crumbling bases using fixative.
7. Fill in any holes in the base.

**Restoring and maintenance**

- 1 -Fully remove any old paint this is loose or in bad condition.
- 2 -Dull down glossy surfaces to ensure good adhesion.
- 3 -On painted bases, check the solidity and anchorage of the paint and the paint type in order to avoid potential incompatibilities. Remove dust and dirt before repainting.
- 4 -Fill any holes in the base using plaster.
- 5 -Mouldy bases should be treated with fungicide.

**WAY OF USE****Application Notes**

- Stir the product until perfectly homogenised.
- Dilute the product according to the porosity and state of the base on the first coat.
- Finish with one or two slightly diluted coats, until the base has full coverage.
- Do not apply the product at temperatures below 5°C or on surfaces exposed to strong sunlight.

**Solvent for dilution and cleaning**

Water

Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	5-20%
Air-mix gun	5-20%
Aerographic gun	10-30%
Low pressure turbo	10-30%

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>Support with mould</b>			
<b>MAX</b>	Fungicida	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Fungicida		Restora P.Plastica con Conservante Antimoho
<b>New work</b>			
<b>MAX</b>	Fijador	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Restora P.Plastica con Conservante Antimoho diluido		Restora P.Plastica con Conservante Antimoho
<b>Old painting in good state</b>			
<b>MAX</b>	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017

<b>STD</b>	Restora P.Plastica con Conservante Antimoho diluido	Restora P.Plastica con Conservante Antimoho
------------	---	---

**Old paintings in bad state**

<b>MAX</b>	Eliminar + Fijador	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Eliminar+ Restora P.Plastica con Conservante Antimoho diluido	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

4 L, 15 L

**FAMILY  
LINE****DESCRIPTION AND NATURE**

Excellent plastic paint with a velvety matte finish, suitable for economical work due to its excellent coverage. With antimould additive.

**USAGES****PROPERTIES**


Does not spead flame  
Fungus and seaweed protector  
Low surface tension  
Velvety flat finish  
Excellent opacity once dry  
Minimum splattering  
Good penetration  
Faint odour  
Does not turn yellow  
Does not spead flame

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017



Good applicability  
Does not turn yellow

## TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,56± 0,05 kg/l
Viscosity	111 +/- 15 PO
Solids in volume	39± 1
Solids in weight	62± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,29 g/l
Aproximated performance by coat	9-11 m <sup>2</sup> /L
Dry to touch	(20°C RH: 60%): -To touch: 1h. -Washing: 25-30 days
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	White.

## SURFACE PREPAIRING

French norm DTU 59.1

### New surfaces

Cement mortars:

1. Wait until fully hardened (min. 30 days).
2. Clean off possible efflorescence with an abrasive jet.
3. Neutralise alkaline surfaces.
4. For polished surfaces: sand down to open the grain.
5. Clean any unusual products from the base.
6. Fix crumbling bases using fixative.
7. Fill in any holes in the base.

Plaster:

1. Wait until the plaster is dry (maximum 20% humidity).
2. Clean any unusual products from the base.
3. Clean off possible efflorescence with an abrasive jet.
4. Control the absorbency of the base using a sealer, fixative or a diluted coat of the same product.
5. For polished surfaces: sand down to open the grain.
6. Fix crumbling bases using fixative.
7. Fill in any holes in the base.

### Restoring and maintenance

- 1 -Fully remove any old paint this is loose or in bad condition.
- 2 -Dull down glossy surfaces to ensure good adhesion.
- 3 -On painted bases, check the solidity and anchorage of the paint and the paint type in order to avoid potential incompatibilities. Remove dust and dirt before repainting.
- 4 -Fill any holes in the base using plaster.
- 5 -Mouldy bases should be treated with fungicide.

## WAY OF USE

### Application Notes

- Stir the product until perfectly homogenised.
- Dilute the product according to the porosity and state of the base on the first coat.
- Finish with one or two slightly diluted coats, until the base has full coverage.
- Do not apply the product at temperatures below 5°C or on surfaces exposed to strong sunlight.

### Solvent for dilution and cleaning

Water

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017

Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	5-20%
Air-mix gun	5-20%
Aerographic gun	10-30%
Low pressure turbo	10-30%

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>Support with mould</b>			
<b>MAX</b>	Fungicida	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Fungicida		Restora P.Plastica con Conservante Antimoho
<b>New work</b>			
<b>MAX</b>	Fijador	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Restora P.Plastica con Conservante Antimoho diluido		Restora P.Plastica con Conservante Antimoho
<b>Old painting in good state</b>			
<b>MAX</b>	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Restora P.Plastica con Conservante Antimoho diluido		Restora P.Plastica con Conservante Antimoho
<b>Old paintings in bad state</b>			
<b>MAX</b>	Eliminar + Fijador	Restora P.Plastica con Conservante Antimoho	Restora P.Plastica con Conservante Antimoho
<b>STD</b>	Eliminar+ Restora P.Plastica con Conservante Antimoho diluido		Restora P.Plastica con Conservante Antimoho

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

412263


# RESTORA ANTIMOHO BLANCA

Fecha de Alta

12-02-2015

Versión

3 - 23/03/2017



## PACKINGS

4 L, 15 L