

412413

Fecha de Alta

19-08-2014

Versión

5 - 05/12/2016

RESTORA PINTURA PLASTICA INTERIOR



FAMILY PINTURAS PLASTICAS

LINE LINEA MATE

DESCRIPTION AND NATURE

Matt acrylic emulsion paint. Excellent washability. Interior and exterior use in mild climates.

USAGES

Indoors
Gypsum Board
Plaster
Cement
Cement
Concrete
Brick
Brick
DIY centres

PROPERTIES

Washability
Washability
Coverage rate
Does not turn yellow
Good adhesion
Good applicability
Does not turn yellow
Odourless when dry
Good adhesion
Coverage rate

TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA PINT.PLAST.INT.BLANCO ROTO
Finish	Matt
Specific weight	1,53± 0,05 kg/l
Viscosity	115 +/- 15 PO
Solids in volume	41± 1
Solids in weight	63± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,58 g/l
Aproximated performance by coat	11-13 m ² /L
Dry to touch	(20°C HR: 60%): 1 h. Lavado: 25-30 day
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	Blanco Roto, Gris Perla, Beige Cálido, Vainilla, Sand, Verde Jade, Azul Soft, Gris Glaciar, Lavanda, Café Creme
Washability	CLASE 3
	AFNOR: NFT. 36005 Famille I Classe 7b2

SURFACE PREPAIRING

French norm DTU 59.1

Fecha de Alta

19-08-2014

Versión

5 - 05/12/2016

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Bad condition surfaces should be anchored properly.
- Cover surface imperfections with plaster or putty.
- Plaster:
- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product.
- Cover surface imperfections with plaster or putty.
- Mildewed surfaces should be treated with fungicide.

Restoring and maintenance

1. Remove off old paint completely,
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty or plaster.
5. Mildewed surfaces should be treated with fungicide.

WAY OF USE

Application Notes

Shake product until perfectly homogenized.

First coat should be dilluted depending on surface conditon and porosity level.

Finish with one or more coats slightly dilluted until surface is totally covered.

Do not apply product at temperatures below 5° C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

WATER

Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	5-30%
Air-mix gun	5-30%
Aerographic gun	10-30%
Low preasure turbo	5-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX	Fijador	Restora Pintura Plastica Interior	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior
Old painting in good state			
MAX	Restora Pintura Plastica Interior muy diluido	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior

Wood

RESTORA PINTURA PLASTICA INTERIOR

Fecha de Alta

19-08-2014

Versión

5 - 05/12/2016

MAX	Selladora	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior

Project

MAX	Fijador	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

8 L



**FAMILY
LINE**

DESCRIPTION AND NATURE

Matt acrylic emulsion paint. Excellent washability. Interior and exterior use in mild climates.

USAGES

PROPERTIES

Washability
Washability
Coverage rate
Does not turn yellow
Good adhesion
Good applicability
Does not turn yellow
Odourless when dry
Good adhesion

Fecha de Alta

19-08-2014

Versión

5 - 05/12/2016



Coverage rate

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,53± 0,05 kg/l
Viscosity	115 +/- 15 PO
Solids in volume	41± 1
Solids in weight	63± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,58 g/l
Aproximated performance by coat	11-13 m ² /L
Dry to touch	(20°C HR: 60%): 1 h. Lavado: 25-30 day
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	Blanco Roto, Gris Perla, Beige Cálido, Vainilla, Sand, Verde Jade, Azul Soft, Gris Glaciar, Lavanda, Café Creme
Washability	CLASE 3
	AFNOR: NFT. 36005 Famille I Classe 7b2

SURFACE PREPARING

French norm DTU 59.1

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Bad condition surfaces should be anchored properly.
- Cover surface imperfections with plaster or putty.
- Plaster:
 - Wait till complete drying of product (20% max. Moisture level).
 - Remove off any foreign product or product remains.
 - Remove off any efflorescences.
 - Use a sealant or matt paste to regulate surface absorption.
 - Extremely polished surfaces should be sandpapered to open pore.
 - Very damaged surfaces should be fixed with suitable product.
 - Cover surface imperfections with plaster or putty.
 - Mildewed surfaces should be treated with fungicide.

Restoring and maintenance

- 1.Remove off old paint completely,
- 2.Brilliant surfaces should be matted to ensure good adherence.
- 3.Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
- 4.Cover surface imperfections with suitable putty or plaster.
- 5.Mildewed surfaces should be treated with fungicide.

WAY OF USE

Application Notes

Shake product until perfectly homogenized.

First coat should be dilluted depending on surface conditon and porosity level.

Finish with one or more coats slightly dilluted until surface is totally covered.

Do not apply product at temperatures below 5° C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

WATER

RESTORA PINTURA PLASTICA INTERIOR



Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	5-30%
Air-mix gun	5-30%
Aerographic gun	10-30%
Low pressure turbo	5-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX	Fijador	Restora Pintura Plastica Interior	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior
Old painting in good state			
MAX	Restora Pintura Plastica Interior muy diluido	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior
Wood			
MAX	Selladora	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior
Project			
MAX	Fijador	Restora Pintura Plastica Interior diluido	Restora Pintura Plastica Interior
STD	Restora Pintura Plastica Interior diluido		Restora Pintura Plastica Interior

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

8 L