

Fecha de Alta

19-02-2015

Versión

3 - 27/04/2017

**FAMILY** PINTURAS PLASTICAS**LINE** LINEA MATE**DESCRIPTION AND NATURE**

Highly acrylic plastic paint, good whiteness and performance. Excellent application, with antimould additive.

USAGES

Indoors

Cement

Plaster

Plaster

Cement

Concrete

Brick

Brick

It can be applied as printing

PROPERTIES

Does not spread flame

Whiteness

Coverage rate

Does not turn yellow

Does not spread flame

Good yield

Does not turn yellow

Water steam transpirable

Odourless when dry

Coverage rate

With antimould additive

TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA PREMIUM BLANCA
Finish	Matt
Specific weight	1,55± 0,05 kg/l
Viscosity	115 +/- 15 PO
Solids in volume	44± 1
Solids in weight	66± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,70 g/l
Aproximated performance by coat	10-12 m ² /L

Dry to touch	(20°C HR: 60%): 1 h. Washing: 25-30 días
--------------	--

Dry to repaint	(20°C HR: 60%): 3-4 h
----------------	-----------------------

Colours	White
---------	-------

AFNOR: NFT. 36005 Famille I Classe 7b2
--

SURFACE PREPAIRING

French norm DTU 59.1

Fecha de Alta

19-02-2015

Versión

3 - 27/04/2017

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Bad condition surfaces should be anchored properly.
- Cover surface imperfections with plaster.

-Plaster:

- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product.
- Cover surface imperfections with plaster or putty.
- Mildewed surfaces should be treated with fungicide.

Restoring and maintenance

- 1.Remove off old paint completely,
- 2.Brilliant surfaces should be matted to ensure good adherence.
- 3.Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
- 4.Cover surface imperfections with suitable putty or plaster.
- 5.Mildewed surfaces should be treated with fungicide.

WAY OF USE**Application Notes**

Shake product until perfectly homogenized.

First coat should be diluted depending on surface condition and porosity level.

Finish with one or more coats slightly diluted until surface is totally covered.

Do not apply product at temperatures below 5° C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	5-30%
Air-mix gun	5-30%
Aerographic gun	10-30%
Low pressure turbo	5-30%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX	Fijador	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium
Old painting in good state			
MAX	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium

Wood

Fecha de Alta

19-02-2015

Versión

3 - 27/04/2017

MAX	Selladora	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium		Restora P.Ptca Mate Premium

Project

MAX	Fijador	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L

**FAMILY
LINE****DESCRIPTION AND NATURE**

Highly acrylic plastic paint, good whiteness and performance. Excellent application, with antimould additive.

USAGES**PROPERTIES**

Does not spead flame
Whiteness
Coverage rate
Does not turn yellow
Does not spead flame
Good yield
Does not turn yellow
Water steam transpirable
Odourless when dry
Coverage rate
With antimould additive

Fecha de Alta

19-02-2015

Versión

3 - 27/04/2017

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,55± 0,05 kg/l
Viscosity	115 +/- 15 PO
Solids in volume	44± 1
Solids in weight	66± 1

VOC Cat. a/BA 75/30 (2007/2010):0,70 g/l

Aproximated performance by coat 10-12 m²/L

Dry to touch (20°C HR: 60%): 1 h. Washing: 25-30 días

Dry to repaint (20°C HR: 60%): 3-4 h

Colours White

AFNOR: NFT. 36005 Famille I Classe 7b2

SURFACE PREPARING

French norm DTU 59.1

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Bad condition surfaces should be anchored properly.
- Cover surface imperfections with plaster.

-Plaster:

- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product.
- Cover surface imperfections with plaster or putty.
- Mildewed surfaces should be treated with fungicide.

Restoring and maintenance

- 1.Remove off old paint completely,
- 2.Brilliant surfaces should be matted to ensure good adherence.
- 3.Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
- 4.Cover surface imperfections with suitable putty or plaster.
- 5.Mildewed surfaces should be treated with fungicide.

WAY OF USE

Application Notes

Shake product until perfectly homogenized.

First coat should be dilluted depending on surface conditon and porosity level.

Finish with one or more coats slightly dilluted until surface is totally covered.

Do not apply product at temperatures below 5° C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%

Fecha de Alta

19-02-2015

Versión

3 - 27/04/2017

Roller	10-20%
Air-less gun	5-30%
Air-mix gun	5-30%
Aerographic gun	10-30%
Low pressure turbo	5-30%

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX	Fijador	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium
Old painting in good state			
MAX	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium
Wood			
MAX	Selladora	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium		Restora P.Ptca Mate Premium
Project			
MAX	Fijador	Restora P.Ptca Mate Premium	Restora P.Ptca Mate Premium
STD	Restora P.Ptca Mate Premium diluido		Restora P.Ptca Mate Premium

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE**PACKINGS**

4 L, 15 L