

RESTORA FACHADAS TEXTURADO BLANCO



FAMILY IMPERMEAB. Y REVEST. FACHADAS / SISTEMAS TINTOMÉTRIC
LINE REVESTIMIENTOS RUGOSOS

DESCRIPTION AND NATURE

Rugged water-based coating for protecting and decorating façades. Good adherence, coverage and resistance to UV rays. Easy to apply. Conceals base imperfections.

USAGES

Outdoors/Indoors
Facades
Cement mortars
Lime Mortars
Porous brick

PROPERTIES

Waterproof
Strong resistance to the atmospherical factors
Does not spread flame
Coverage rate
Does not turn yellow
Good adhesion
Strong resistance to the atmospherical factors
Does not spread flame
Does not turn yellow
Water steam transpirable
Good adhesion
Coverage rate
Odourless

TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA FACHADAS TEXTURADO BLANCO
Finish	Rough
Specific weight	1,79± 0,05 kg/l
Solids in volume	63± 1
Solids in weight	81± 1
VOC	Cat. c/BA 75/40 (2007/2010):0,83 g/l
Aproximated performance by coat	1,5-2 m ² /L

Dry to touch	(20°C HR: 60%): 1-3 h. Washability: 25-30 days
Dry to repaint	(20°C HR: 60%): 24h
Colours	White 103

SURFACE PREPAIRING

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Surfaces in bad conditions should be anchored with suitable fixer.
- Cover surface imperfections with plaster or putty.

Fecha de Alta

04-12-2015

Versión

3 - 29/03/2017

- Plaster:
- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product.
- Cover surface imperfections with plaster or putty.
- Mildewed surfaces should be treated with fungicide.

Restoring and maintenance

1. Remove off old paints completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring in painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty of plaster.
5. Mildewed surfaces should be treated with fungicide.
6. Absorbent surfaces should be sealed with same colour smooth coverings.

WAY OF USE

Application Notes

- Shake product until perfectly homogenized.
- This product should be diluted depending on surface condition and porosity level.
- It is advisable to prepare the base with a smooth coating of the same colour to prevent excessive absorption.
- Do not apply the product at temperatures below 5°C, above 35 °C, or to surfaces exposed to strong sunlight.
- Do not apply when rain is imminent risk

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Roller	0-5%
Stucco spray gun	0-5%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Support with mould			
MAX	Fungicida	Revestimiento liso diluido	Restora Rev. Fachadas Texturado
STD	Fungicida		Restora Rev. Fachadas Texturado
New work			
MAX	Fijador		Restora Rev. Fachadas Texturado
STD	Revestimiento liso diluido		Restora Rev. Fachadas Texturado
Old painting in good state			
MAX	Revestimiento liso diluido		Restora Rev. Fachadas Texturado
STD			Restora Rev. Fachadas Texturado
Support weak			
MAX	Fijador	Revestimiento liso diluido	Restora Rev. Fachadas Texturado
STD	Revestimiento liso diluido		Restora Rev. Fachadas Texturado
Old paintings in bad state			
MAX	Eliminar + Fijador	Revestimiento liso diluido	Restora Rev. Fachadas Texturado
STD	Eliminar + Revestimiento liso diluido		Restora Rev. Fachadas Texturado

RESTORA FACHADAS TEXTURADO BLANCO

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L