

RESTORA FACHADAS LISO BLANCO



FAMILY IMPERMEAB. Y REVEST. FACHADAS

LINE REVESTIMIENTOS AL SILOXANO

DESCRIPTION AND NATURE

Water-repellent smooth coating for the protection and decoration of façades. With good resistance to the elements. Very easy to apply and cover. Breathable to water vapor and impermeable to rainwater. With antimould additive.

USAGES

Outdoors/Indoors

Cement

Concrete

Facades

Cement mortars

Porous brick

PROPERTIES

Does not turn yellow

Waterproof

Strong resistance to the atmospherical factors

Water steam transpirable

Does not spread flame

Working smoothness

Light & climatic resistant colours

Does not present tacking

Strong resistance to the atmospherical factors

Does not spread flame

Elasticity enough to resist the normal structural movements

Easy application

With antimould additive

TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA FACHADAS LISO BLANCO
Finish	Smooth matt
Specific weight	1,51 ± 0,05 kg/l
Viscosity	104 +/- 20 PO
Solids in volume	41 ± 1
Solids in weight	63 ± 1
VOC	Cat. c/BA 75/40 (2007/2010): 1,02 g/l
Aproximated performance by coat	6-9 m ² /L

Dry to touch (20°C HR: 60%): 1 h Washing: 25-30 days

Dry to repaint (20°C HR: 60%): 4-6 h

Colours White, Bone, Ivory Luminous, Blue, Albero, Intense Tile, English Red and Gray

- AFNOR NFT 36005-Famillie I-Classe 7b2/10c sous-cat. VOC máx=30 g/l

SURFACE PREPAIRING

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).

RESTORA FACHADAS LISO BLANCO

Fecha de Alta

11-02-2015

Versión

4 - 23/03/2017

- Remove off any efflorescences by abrasive jet
- Neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Bad condition surfaces should be anchored properly.
- Cover surface imperfections.

Plaster:

- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product.
- Cover surface imperfections with plaster or putty.

Restoring and maintenance

1. Fully remove any old paint that is loose or in bad condition.
2. Dull down glossy surfaces to ensure good adhesion.
3. On painted bases, check the solidity and adhesion of the paint and the type of paint to avoid potential incompatibilities and remove dust and dirt before repainting.
4. Use plaster to fill any defects in the base.
5. Treat mouldy bases with fungicide.

WAY OF USE

Application Notes

- Shake product until perfectly homogenized.
- For the application of first layer, this product should be dilluted depending on suface condition and porosity level.
- Finish with one or more coats slightly dilluted until surface is totally covered.
- Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunsshine. Do not apply in very humid or wet weather.
- It is not recommended to wash the walls until after 24 days.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low preasure turbo	10-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Selladora al agua	Restora Revestimiento Fachadas	Restora Revestimiento Fachadas
STD	Restora Revestimiento Fachadas diluido		Restora Revestimiento Fachadas
Old painting in good state			
MAX	Restora Revestimiento Fachadas diluido	Restora Revestimiento Fachadas	Restora Revestimiento Fachadas
STD	Restora Revestimiento Fachadas diluido		Restora Revestimiento Fachadas
Old paintings in bad state			

RESTORA FACHADAS LISO BLANCO

Fecha de Alta

11-02-2015

Versión

4 - 23/03/2017

MAX	Eliminar + Imprimación Fijadora	Restora Revestimiento Fachadas	Restora Revestimiento Fachadas
STD	Eliminar + Restora Revestimiento Fachadas diluido		Restora Revestimiento Fachadas

Support weak

MAX	Imprimación fijadora	Restora Revestimiento Fachadas	Restora Revestimiento Fachadas
STD	Restora Revestimiento Fachadas diluido		Restora Revestimiento Fachadas

Cement

MAX	Imprimación Fijadora	Restora Revestimiento Fachadas	Restora Revestimiento Fachadas
STD	Restora Revestimiento Fachadas diluido		Restora Revestimiento Fachadas

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L