

RESTORA ANTIMANCHAS BLANCO



FAMILY

PRODUCTOS PARA USO ESPECIFICO

LINE

ANTIHUMEDAD Y ANTIMANCHAS

DESCRIPTION AND NATURE

Paint formulated to block and isolate smoke stains, dry damp stains, colouring pencils, coffee... thus preventing them from reappearing, while completely covering them and providing a decorative finish.

USAGES

Indoors
Cement
Plaster
Plaster
Cement
Concrete
Spotted smoke, nicotine, oil
Smoke, nicotine

PROPERTIES

Adherence
Anti-spots
Applicability
Penetration power
No sanding necessary for repainting. Non expensive maintenance
It controls absorption
Odourless when dry
Penetration power

TECHNICAL CHARACTERISTICS

Referencia Color	RESTORA ANTIMANCHAS BLANCO
Finish	Matt
Specific weight	1,49± 0,05 kg/l
Viscosity	180 +/- 30 PO
Solids in volume	43± 1
Solids in weight	71± 1
VOC	Cat. i/BD 600/500 (2007/2010): 469,00 g/l
Aproximated performance by coat	3-6 m ² /L
Dry to touch	(20°C HR: 60%): 2-4 horas
Dry to repaint	(20°C HR: 60%): mín 24 horas
Colours	White

SURFACE PREPARING

New surfaces

Cement mortar:
-Wait till complete drying of product (30 days minimum).
-Surface should be totally dry (maximum 20% moisture content).
-Remove off any efflorescences and neutralize alkaline surfaces.
-Extremely polished surfaces should be sanpapered to open pores.
-Remove off any foreing products or remains.
-Only apply product on dry and free of dust surfaces
-Cover surface imperfections with suitable plaster.

RESTORA ANTIMANCHAS BLANCO

Fecha de Alta

30-06-2015

Versión

4 - 29/03/2017

-For extreme cases with anchoring problems, apply Fijalite.

New wood:

-Surface should be free of any foreign products or remains.

-Apply on wood with less than 20% moisture content.

-Apply on wood in good condition, dry and free of grease and dust.

-Sandpaper and eliminate any remains in joints and mechanical faults.

-Old wood should be previously sanded and primed. Remove any dust by brushing off or using any other mechanical system.

-As a fungicide prevention treatment, we recommend applying a base coat.

-Iron or steel:

Remove surface off any rust, grease or dirt and prime with Imprimación Antioxidante or Minio.

Restoring and maintenance

-Old paint in bad condition and with poor adhesion should be removed.

-Product should be applied directly on oil, grease, nicotine or smoke stains.

-Extreme cases should be previously cleaned with hot water and detergents.

-Leave to dry and proceed to paint.

WAY OF USE

Application Notes

-Shake product until perfectly homogenized.

-Follow application guidelines as shown on table below.

-Restora Antimanchas Blanco can be applied with excellent results with just one coat, although in exceptional cases it is recommended to double the number of coats.

-Do not apply product at high temperatures or on overheated surfaces exposed to sunshine.

-Do not apply when moisture content is over 80%.

-Keep room well ventilated while product is drying.

Solvent for dilution and cleaning

Disolvente sintéticos y grasos, Universal, Simil Aguarrás

Way of use	Aproximate dilution
Painting brush	al uso
Roller	al uso
Air-less gun	10-25%
Air-mix gun	10-25%
Aerographic gun	10-25%
Low pressure turbo	10-25%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Metal decoration			
MAX	Imprimación Antioxidante	Restora Antimanchas Blanco	
STD	Minio		Restora Antimanchas Blanco
Inner painted old work in good state			
MAX			
STD	Restora Antimanchas Blanco		Restora Antimanchas Blanco
Inner painted old work in good state			
MAX		Restora Antimanchas Blanco	
STD	Fijador		Restora Antimanchas Blanco
New work			
MAX	Fijador	Restora Antimanchas Blanco	

RESTORA ANTIMANCHAS BLANCO

Fecha de Alta

30-06-2015

Versión

4 - 29/03/2017

STD	Restora Antimanchas Blanco	Restora Antimanchas Blanco
------------	----------------------------	----------------------------

Paints with stains

MAX

STD	Restora Antimanchas Blanco	Restora Antimanchas Blanco
------------	----------------------------	----------------------------

Old/New interior Wood

MAX	Imprimación poro abierto para madera	Restora Antimanchas Blanco
------------	--------------------------------------	----------------------------

STD	Restora Antimanchas Blanco	Restora Antimanchas Blanco
------------	----------------------------	----------------------------

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L



FAMILY LINE

DESCRIPTION AND NATURE

Paint formulated to block and isolate smoke stains, dry damp stains, colouring pencils, coffee... thus preventing them from reappearing, while completely covering them and providing a decorative finish.

USAGES

PROPERTIES


- Adherence
- Anti-spots
- Applicability
- Penetration power
- No sanding necessary for repainting. Non expensive maintenance
- It controls absorption
- Odourless when dry

Fecha de Alta

30-06-2015

Versión

4 - 29/03/2017



Penetration power

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,49± 0,05 kg/l
Viscosity	180 +/- 30 PO
Solids in volume	43± 1
Solids in weight	71± 1
VOC	Cat. i/BD 600/500 (2007/2010): 469,00 g/l
Aproximated performance by coat	3-6 m ² /L
Dry to touch	(20°C HR: 60%): 2-4 horas
Dry to repaint	(20°C HR: 60%): min 24 horas
Colours	White

SURFACE PREPAIRING

New surfaces

Cement mortar:

- Wait till complete drying of product (30 days minimum).
- Surface should be totally dry (maximum 20% moisture content).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Only apply product on dry and free of dust surfaces
- Cover surface imperfections with suitable plaster.
- For extreme cases with anchoring problems, apply Fijalite.

New wood:

- Surface should be free of any foreign products or remains.
- Apply on wood with less than 20% moisture content.
- Apply on wood in good condition, dry and free of grease and dust.
- Sandpaper and eliminate any remains in joints and mechanical faults.
- Old wood should be previously sandpapered and primed. Remove any dust by brushing off or using any other mechanical system.
- As a fungicide prevention treatment, we recommend applying a base coat.

-Iron or steel:

Remove surface off any rust, grease or dirt and prime with Imprimación Antioxidante or Minio.

Restoring and maintenance

- Old paint in bad condition and with poor adhesion should be removed.
- Product should be applied directly on oil, grease, nicotine or smoke stains.
- Extreme cases should be previously cleaned with hot water and detergents.
- Leave to dry and proceed to paint.

WAY OF USE

Application Notes

- Shake product until perfectly homogenized.
- Follow application guidelines as shown on table below.
- Restora Antimanchas Blanco can be applied with excellent results with just one coat, although in exceptional cases it is recommended to double the number of coats.
- Do not apply product at high temperatures or on overheated surfaces exposed to sunshine.
- Do not apply when moisture content is over 80%.
- Keep room well ventilated while product is drying.

Solvent for dilution and cleaning

Disolvente sinteticos y grasos, Universal, Simil Aguarrás

Fecha de Alta

30-06-2015

Versión

4 - 29/03/2017

Way of use	Aproximate dilution
Painting brush	al uso
Roller	al uso
Air-less gun	10-25%
Air-mix gun	10-25%
Aerographic gun	10-25%
Low pressure turbo	10-25%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Metal decoration			
MAX	Imprimación Antioxidante	Restora Antimanchas Blanco	
STD	Minio		Restora Antimanchas Blanco
Inner painted old work in good state			
MAX			
STD	Restora Antimanchas Blanco		Restora Antimanchas Blanco
Inner painted old work in good state			
MAX		Restora Antimanchas Blanco	
STD	Fijador		Restora Antimanchas Blanco
New work			
MAX	Fijador	Restora Antimanchas Blanco	
STD	Restora Antimanchas Blanco		Restora Antimanchas Blanco
Paints with stains			
MAX			
STD	Restora Antimanchas Blanco		Restora Antimanchas Blanco
Old/New interior Wood			
MAX	Imprimación poro abierto para madera	Restora Antimanchas Blanco	
STD	Restora Antimanchas Blanco		Restora Antimanchas Blanco

SECURITY


Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

413105

Fecha de Alta
30-06-2015
Versión
4 - 29/03/2017

RESTORA ANTIMANCHAS BLANCO



NOTE

PACKINGS

4 L