

Fecha de Alta

19-08-2014

Versión

2 - 05/04/2017

**FAMILY** TRATAMIENTOS DE LA MADERA**LINE** RESTAURACION**DESCRIPTION AND NATURE**

Biodegradable and non-toxic paint stripper. Effectively removes paints and varnishes. Specific for wood. It does not damage, deteriorate or alter the colour. Free from acid, alkalis and methylene chloride.

USAGES

Outdoors/Indoors

Metal

PROPERTIES

Applicability

Ecological

Open time

It removes easily the paintings , by contact and some scrapping

do not enerates dust

Paint remover specially for wood

Eliminates paints and varnishes

Does not harms wood

Does not alter its colour

Without acids

Without alcalis

Without cloruro metileno

TECHNICAL CHARACTERISTCS

Referencia Color RESTORA GEL DECAPANTE

Finish Transparent

Specific weight 0,96± 0,05 kg/l

Viscosity 44 +/- 5 PO

Solids in volume 3± 1

Solids in weight 3± 1

Aproximated performance by coat 3-6 m²/L

Dry to touch Tiempo de trabajo: 10-20 min

Dry to repaint (20°C HR: 60%): 6 h

Colours Translucent, whitish

SURFACE PREPAIRING**New surfaces**

Not applicable

Restoring and maintenance

See next section Application. New wood not applicable

WAY OF USE**Application Notes**

1. Slowly mix the product with a spatula.

Fecha de Alta

19-08-2014

Versión

2 - 05/04/2017

2. A prior degreasing and sanding is recommended on very well adhered bases, although in most cases, a previous cleaning with hot soapy water is usually sufficient. Allow to dry.
3. Applicable on well-adhered bases. Usually it is not necessary to open the pores. In cases of excessively closed pores, open them with wood sandpaper.
4. It is highly recommended to test the product on a small surface to verify its suitability. In case of doubt please contact our Technical Department.
5. Before repainting, a proper washing with clean water is recommended. Allow to dry.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Uso
Roller	Uso
Pallete / spatula	Uso

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Polyurethane lacquers and varnishes			
MAX	Restora Gel Decapante	Restora Gel Decapante	Sistema Gama Madera
STD	Restora Gel Decapante		Sistema Gama Madera
Nitrocellulose lacquers and varnishes			
MAX	Restora Gel Decapante	Restora Gel Decapante	Sistema Gama Madera
STD	Restora Gel Decapante		Sistema Gama Madera
Enamels and synthetic varnishes			
MAX	Restora Gel Decapante	Restora Gel Decapante	Sistema Gama Madera
STD	Restora Gel Decapante		Sistema Gama Madera
Paints and watter lasures			
MAX	Restora Gel Decapante	Restora Gel Decapante	Sistema Gama Madera
STD	Restora Gel Decapante		Sistema Gama Madera

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L